



PREMIUM PORTABLE UNITS

Midea 'Premium Portable' air conditioning units are available in either 2.5kW or 3.5kW. The energy efficient units are easy to control via the MSmarthome APP. With a simple swipe, the units can be turned on/off and the appropriate mode and temperature selected.

VOICE AND APP CONTROL

All portable units can be controlled by the MSmartHome App and can be used with Alexa and Google Home voice commands.

ENERGY SAVING

The power consumption of the unit is equal to 0.5 W. This allows great energy savings.

SLEEP MODE FUNCTION

With a precise temperature control system, "sleep mode" creates an ideal climate in your room so you can wake up comfortable and fully refreshed.

EASY TO MOVE

The unit sits on easy glide castor wheels, making it easy to transport and move the unit into different rooms.

SELF EVAPORATING

The water collected is automatically evaporated, so there is no need to worry about emptying trays.

AUTOMATIC RESTART

In the event of a power failure, the unit restarts with the settings previously in use.

LED DISPLAY

The LED display shows the temperature of the unit and gives an indication of any errors, allowing for auto protection and self diagnosis.

24 HOUR TIMER


Use the 24 Hour/7 Day timer via the APP to control the portable unit.



ECO timer



No Drain-Pipe Required



Easy to clean filter



Power cord tidy design



360° Castor Wheels



Voice Control



MSmartHome



PREMIUM PORTABLE UNITS

MODEL			MPPFA1-09CRN7	MPPFB1-12CRN7
Power supply (Powered via 3 Pin Plug)		Ph-V-Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Cooling	Capacity	Btu/h	9000	12000
	Capacity	KW	2.5	3.5
	Input	W	1015	1350
	Current	A	4.5	5.9
	EER	W/W	2.6	2.6
	Energy Efficiency Class		A	A
Moisture Removal		L/h	2.3	3.189
Rated Input Consumption		W	1200	1600
Rated Current		A	6.4	8.3
Starting Current		A	20	25
Indoor Air Flow (Hi/Mi/Lo)		m3/h	380/350/304	400/360/320
Indoor Side Noise Level (Hi/Mi/Lo)		dB(A)	53.9/52.6/51.3	53/51/50
Sound Power Level (Hi)		dB(A)	65	63
Power Consumption in Standby Mode		W	0.5	0.5
Refrigerant Type	Type		R290	R290
	GWP		3	3
	Charged Quantity	kg	0.21	0.24
	CO2 Quantitiy	kg	0	0
Design Pressure		MPa	2.6/1.0	2.6/1.0
Plug Type			1.5x3/VDE	1.5x3/VDE
Control Type			Remote Control	Remote Control
Operation Temp (room temp)		°C	17-35	17-35
Dimension (W*D*H)		mm	435x342x720	458x373x775
Packaging (W*D*H)		mm	475x410x870	510x440x880
Net/Gross Weight		kg	26.31/32.67	31.2/34.6