

COMPACT CEILING CONCEALED DUCT

MID STATIC PRESSURE

- CM18F / CM24F / UM30F / UM36F

UUA1 ULO

UUB1 U20

UUC1 U40



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
: www.eurovent-certification.com



COMBINATION					18	24	30	36
Capacity	Cooling	Min. / Rated / Max.	kW		1.8 / 5.0 / 5.6	2.7 / 6.8 / 7.5	3.0 / 7.5 / 8.3	3.8 / 9.5 / 10.5
	Heating	Min. / Rated / Max.	kW		2.2 / 5.5 / 6.7	3.0 / 7.4 / 8.5	3.2 / 8.0 / 8.8	4.3 / 10.8 / 11.5
Power Input (Set)	Cooling	Min. / Rated / Max.	kW		0.35 / 1.67 / 1.92	0.50 / 2.34 / 2.81	0.50 / 2.57 / 3.08	0.60 / 3.16 / 3.86
	Heating	Min. / Rated / Max.	kW		0.32 / 1.58 / 1.77	0.40 / 2.17 / 2.82	0.50 / 2.25 / 2.93	0.60 / 3.03 / 3.48
Running Current	Cooling	Rated	A		7.4	10.3	11.0	14.0
	Heating	Rated	A		7.0	9.7	9.7	13.4
EER / COP			kWh / kWh		3.00 / 3.50	2.91 / 3.41	2.92 / 3.56	3.01 / 3.57
SEER / SCOP			kWh / kWh		6.1 / 3.8	5.8 / 4.1	5.6 / 3.9	5.9 / 4.0
Pdesign	Cooling @ 35°C		kW		5	6.8	7.5	9.5
	Heating @ -10°C		kW		2.8	4.1	4.3	5.5
Seasonal Energy Label	Cooling / Heating		-		A++ / A	A+ / A+	A+ / A	A+ / A+
Annual Energy Consumption	Cooling / Heating		kWh		287 / 1,032	410 / 1,400	469 / 1,544	564 / 1,924
Dehumidification Rate			l/h		1.2	2.5	2.6	3.2
ODU Sound Pressure Level	Cooling / Heating	Rated	dB(A)		49 / 52	48 / 53	50 / 54	54 / 56
ODU Sound Power Level	Cooling	Rated	dB(A)		65	65	67	70
Piping Connections	Liquid		mm (inch)		Ø6.35 (1/4)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)
	Gas		mm (inch)		Ø12.7 (1/2)	Ø15.88 (5/8)	Ø15.88 (5/8)	Ø15.88 (5/8)
	Connections Method		-		Flared	Flared	Flared	Flared
Operation (Outdoor)	Range	Cooling	Min. / Max.	°C	-10 / 50	-10 / 48	-10 / 48	-20 / 50
		Heating	Min. / Max.	°C	-10 / 18	-15 / 18	-15 / 18	-15 / 18

INDOOR					CM18F N10	CM24F N10	UM30F N10	UM36F N20
Power Supply			Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Input (IDU)		H / M / L	W		150 / 130 / 110	180 / 150 / 130	220 / 200 / 180	183 / 134 / 101
Air Flow Rate		H / M / L	m ³ /min		16.5 / 14.5 / 13	18 / 16.5 / 14.5	22 / 20 / 18	32 / 28 / 24
Dimensions	Body	W x H x D	mm		900 x 270 x 700	900 x 270 x 700	900 x 270 x 700	1,250 x 270 x 700
Weight	Body		kg		24.6	24.6	26.2	38.5
Sound Pressure Level	Cooling	H / M / L	dB(A)		34 / 32 / 30	35 / 34 / 32	37 / 35 / 34	36 / 34 / 33
Sound Power Level	Cooling	Max.	dB(A)		59	60	62	60
Piping Connections	Drain (Natural Drainage)	O.D. / I.D.	mm		Ø25.4 / 19.4	Ø25.4 / 19.4	Ø25.4 / 19.4	Ø25.4 / 19.4
	Drain (Using Drain Pump)	O.D. / I.D.	mm		Ø32.0 / 26.0	Ø32.0 / 26.0	Ø32.0 / 26.0	Ø32.0 / 26.0

OUTDOOR					UUA1 ULO	UUB1 U20	UUC1 U40
Power Supply			Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Circuit Breaker		Min.	A		15	20	25
Power Supply Cable (Included Earth)			No x mm ³		3C x 1.5	3C x 2.5	3C x 2.5
Dimensions	Net	W x H x D	mm		770 x 545 x 288	870 x 650 x 330	950 x 834 x 330
Weight	Net		kg		33.3	44.5	57.7
Compressor	Type		-		Twin Rotary	Twin Rotary	Twin Rotary
	Type		-		R32	R32	R32
Refrigerant	GWP (Global Warming Potential)		-		675	675	675
	Precharged Amount		kg		1	1.2	1.9
	t-CO ₂ eq		-		0.675	0.81	1.283
	Additional Charge (After 7.5m)		g/m		20	40	40
Fan	Air Flow Rate	Rated	m ³ /min x No.		28 x 1	50 x 1	58 x 1
Total Piping Length		Min. / Max.	m		5 / 30	5 / 35	5 / 50
Piping Elevation	IDU - ODU	Max.	m		30	30	30