

Specifications Table for FTXA-CS

				FTXA20C2V1BS	FTXA25C2V1BS	FTXA35C2V1BS	FTXA42C2V1BS	FTXA50C2V1BS		
Power input	Cooling		Nom.	kW	0.020	0.022	0.023	0.028	0.030	
	Heating		Nom.	kW	0.020	0.020	0.220	0.036	0.039	
Casing	Colour				Silver	Silver	Silver	Silver	Silver	
Dimensions	Unit		Height	mm	295	295	295	295	295	
			Width	mm	798	798	798	798	798	
			Depth	mm	189	189	189	189	189	
Weight	Unit			kg	11.5	11.5	11.5	11.5	11.5	
Fan	Air flow rate	Cooling	High	m ³ /min	11.0	11.5	11.9	13.1	13.5	
			Medium	m ³ /min	8.2	8.6	8.6	9.8	10.4	
			Low	m ³ /min	6.1	6.1	6.1	7.2	7.6	
			Silent operation	m ³ /min	4.6	4.6	4.6	4.6	5.2	
			Heating	High	m ³ /min	10.9	11.1	11.5	14.6	15.1
				Medium	m ³ /min	8.7	9.0	9.0	10.5	11.1
				Low	m ³ /min	6.4	6.4	6.4	7.7	8.2
				Silent operation	m ³ /min	4.5	4.5	4.5	5.2	5.7
Sound power level	Cooling			dBA	57	57	60	60	60	
Sound pressure level	Cooling		High	dBA	39	40	41	45	46	
			Medium	dBA	32	33	33	37	39	
			Low	dBA	25	25	25	29	31	
			Silent operation	dBA	19	19	19	21	24	
	Heating		High	dBA	39	40	41	45	46	
			Medium	dBA	32	33	33	37	42	
			Low	dBA	25	25	25	29	33	
			Silent operation	dBA	19	19	19	21	24	
Refrigerant	GWP				675.0	675.0	675.0	675.0	675.0	
Piping connections	Liquid		OD	mm	6.35	6.35	6.35	6.35	6.35	
	Gas		OD	mm	9.50	9.50	9.50	9.50	12.70	
	Drain				18	18	18	18	18	
Control systems	Infrared remote control				ARC466A85	ARC466A85	ARC466A85	ARC466A85	ARC466A85	
	Wired remote control				BRC073A1	BRC073A1	BRC073A1	BRC073A1	BRC073A1	
Standard Accessories	Installation manual				1	1	1	1	1	
	Operation manual				1	1	1	1	1	
	Air filter				2	2	2	2	2	
	Infrared remote control				1	1	1	1	1	
	Remote controller mounting plate				1	1	1	1	1	
	Screw bag				1	1	1	1	1	
	Screw cover				2	2	2	2	2	
	AAA dry-cell batteries				2	2	2	2	2	
	General safety precautions				1	1	1	1	1	
	Power supply	Name				V1	V1	V1	V1	V1
Phase				1~	1~	1~	1~	1~		
Frequency			Hz	50	50	50	50	50		
Voltage			V	220-240	220-240	220-240	220-240	220-240		