

Specifications Table for FTXJ-AS

				FTXJ20A2V1BS	FTXJ25A2V1BS	FTXJ35A2V1BS	FTXJ42A2V1BS	FTXJ50A2V1BS			
Power input	Cooling	Nom.	kW	0.02	0.022	0.024	0.028	0.031			
	Heating	Nom.	kW	0.021	0.022	0.024	0.036	0.039			
Casing	Colour			Silver	Silver	Silver	Silver	Silver			
Dimensions	Unit	Height	mm	305	305	305	305	305			
		Width	mm	900	900	900	900	900			
		Depth	mm	212	212	212	212	212			
Weight	Unit		kg	12	12	12	12	12			
Fan	Air flow rate	Cooling	High	m ³ /min	11	11.4	11.8	13	13.5		
			Medium	m ³ /min	8.4	8.6	8.6	9.5	10.4		
			Low	m ³ /min	6	6	6	7.2	7.6		
			Silent operation	m ³ /min	4.6	4.6	4.6	4.6	5.2		
	Heating	High	High	m ³ /min	11.1	11.3	11.7	14.4	15.0		
			Medium	m ³ /min	8.7	9	9	10.5	11.1		
			Low	m ³ /min	6.4	6.4	6.4	7.7	8.2		
			Silent operation	m ³ /min	4.6	4.6	4.6	5.2	5.7		
			Sound power level	Cooling		dB(A)	57	57	60	60	60
				Sound pressure level	Cooling	High	dB(A)	39	40	41	45
Medium	dB(A)	32	33			33	37	39			
Low	dB(A)	25	25			25	29	31			
Silent operation	dB(A)	19	19			19	21	24			
Heating	High	High	dB(A)		39	40	41	45	46		
		Medium	dB(A)		32	33	33	37	42		
		Low	dB(A)		25	25	25	29	33		
		Silent operation	dB(A)		19	19	19	21	24		
		Refrigerant	GWP			675	675	675	675	675	
		Piping connections	Liquid		OD	mm	6.35	6.35	6.35	6.35	6.35
Gas	OD			mm	9.5	9.5	9.5	12.7	12.7		
Drain				18	18	18	18	18			
Control systems	Infrared remote control			ARC488A1S	ARC488A1S	ARC488A1S	ARC488A1S	ARC488A1S			
	Wired remote control			BRC073A1	BRC073A1	BRC073A1	BRC073A1	BRC073A1			
Standard Accessories	Installation manual			1	1	1	1	1			
	Wireless remote control			1	1	1	1	1			
	Screw cover			2	2	2	2	2			
	AAA dry-cell batteries			2	2	2	2	2			
	General safety precautions			1	1	1	1	1			
	Operation manual			1	1	1	1	1			
	Titanium apatite deodorizing filter			1	1	1	1	1			
	Silver particle filter			1	1	1	1	1			
	Mounting plate			1	1	1	1	1			
	Remote control holder			1	1	1	1	1			
	Screw bag			1	1	1	1	1			
	Power supply	Name			V1	V1	V1	V1	V1		
		Phase			1~	1~	1~	1~	1~		
Frequency			Hz	50	50	50	50				
Voltage			V	220-240	220-240	220-240	220-240				