

Specifications Table for FTXF-E

| | | | | FTXF20E5V1B | FTXF25E5V1B | FTXF35E5V1B | FTXF42E5V1B | | | |
|----------------------------|----------------------|----------------------|-------------------------|--|--|--|--|----------|----------|-----|
| Power input | Cooling | Nom. | kW | 0.023 | 0.023 | 0.029 | 0.040 | | | |
| | Heating | Nom. | kW | 0.023 | 0.023 | 0.029 | 0.040 | | | |
| Casing | Colour | | | White | White | White | White | | | |
| Dimensions | Unit | Height | mm | 286 | 286 | 286 | 286 | | | |
| | | Width | mm | 770 | 770 | 770 | 770 | | | |
| | | Depth | mm | 225 | 225 | 225 | 225 | | | |
| Weight | Unit | | kg | 8.00 | 8.00 | 8.50 | 9.00 | | | |
| Fan | Air flow rate | Cooling | High | m ³ /min | 9.8 | 10.0 | 11.5 | 12.6 | | |
| | | | Medium | m ³ /min | 8 | 8 | 8 | 9 | | |
| | | | Low | m ³ /min | 6.0 | 6.2 | 6.4 | 6.9 | | |
| | | | Heating | High | m ³ /min | 10.4 | 10.4 | 11.9 | 12.8 | |
| | | | | Medium | m ³ /min | 8.3 | 8.4 | 8.6 | 8.8 | |
| | | | | Low | m ³ /min | 6.2 | 6.4 | 6.5 | 6.7 | |
| | | | | Silent operation | High | m ³ /min | 4.3 | 4.3 | 4.4 | 4.9 |
| | | | | | Medium | m ³ /min | 4.3 | 4.3 | 4.4 | 4.9 |
| | | | | | Low | m ³ /min | 4.3 | 4.3 | 4.4 | 4.9 |
| Sound power level | Cooling | | dB(A) | 53.0 | 54.0 | 54.0 | 59.0 | | | |
| | Heating | | dB(A) | 55.0 | 55.0 | 56.0 | 59.0 | | | |
| Sound pressure level | Cooling | High | dB(A) | 39.0 | 40.0 | 43.0 | 45.0 | | | |
| | | Medium | dB(A) | 33.0 | 33.0 | 34.0 | 36.0 | | | |
| | | Low | dB(A) | 25.0 | 26.0 | 27.0 | 30.0 | | | |
| | Heating | High | dB(A) | 39.0 | 40.0 | 40.0 | 44.0 | | | |
| | | Medium | dB(A) | 34.0 | 34.0 | 35.0 | 34.0 | | | |
| | | Low | dB(A) | 28.0 | 28.0 | 29.0 | 28.0 | | | |
| Piping connections | Liquid | OD | mm | 6 | 6 | 6 | 6 | | | |
| | | Gas | OD | mm | 9.50 | 9.50 | 9.50 | 9.50 | | |
| | | | Drain | | 18 | 18 | 18 | 18 | | |
| | Control systems | | Infrared remote control | | | ARC470A1 | ARC470A1 | ARC470A1 | ARC470A1 | |
| | | Wired remote control | | | BRC073A1 | BRC073A1 | BRC073A1 | BRC073A1 | | |
| | Standard Accessories | Installation manual | | | 1 | 1 | 1 | 1 | | |
| Operation manual | | | 1 | 1 | 1 | 1 | | | | |
| Infrared remote control | | | 1 | 1 | 1 | 1 | | | | |
| AAA dry-cell batteries | | | 2 | 2 | 2 | 2 | | | | |
| Remote control holder | | | 1 | 1 | 1 | 1 | | | | |
| Mounting plate | | | 1 | 1 | 1 | 1 | | | | |
| Indoor unit fixing screws | | | 2 | 2 | 2 | 2 | | | | |
| General safety precautions | | | 1 | 1 | 1 | 1 | | | | |
| Power supply | Phase | | | 1~ | 1~ | 1~ | 1~ | | | |
| | Frequency | | Hz | 50 | 50 | 50 | 50 | | | |
| | Voltage | | V | 220-440 | 220-440 | 220-440 | 220-440 | | | |
| Notes | | | | (1) - Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m | (1) - Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m | (1) - Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m | (1) - Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m | | | |
| | | | | (2) - Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal) | (2) - Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal) | (2) - Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal) | (2) - Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal) | | | |
| | | | | (3) - See separate drawing for electrical data | (3) - See separate drawing for electrical data | (3) - See separate drawing for electrical data | (3) - See separate drawing for electrical data | | | |