

Specifications Table for FTXP-N9

				FTXP20N5V1B9	FTXP25N5V1B9	FTXP35N5V1B9	FTXP50N5V1B9	
Power input	Cooling	Nom.	kW	0.021	0.023	0.032	0.04	
	Heating	Nom.	kW	0.023	0.023	0.032	0.04	
Casing	Colour			White	White	White	White	
Dimensions	Unit	Height	mm	286	286	286	286	
		Width	mm	770	770	770	770	
		Depth	mm	225	225	225	225	
Weight	Unit		kg	9	9	9	9	
Fan	Air flow rate	Cooling	High	m ³ /min	9.6	9.9	11.5	11.8
			Medium	m ³ /min	7.5	7.5	8.3	9.3
			Low	m ³ /min	5.6	5.8	6.3	7.6
			Silent operation	m ³ /min	4.4	4.4	4.5	6
		Heating	High	m ³ /min	10.6	10.6	11.5	11.9
			Medium	m ³ /min	8.6	8.6	9	9.5
			Low	m ³ /min	6.6	6.6	7	8.2
			Silent operation	m ³ /min	5	5	5.1	7.4
	Sound power level	Cooling			dB(A)	55	58	59
Heating			dB(A)	55	58	61		
Sound pressure level	Cooling	High	dB(A)	39	40	43	46	
		Medium	dB(A)	33	33	34	39	
		Low	dB(A)	25	26	27	34	
			Silent operation	dB(A)	19	19	20	27
		Heating	High	dB(A)	39	40	40	44
			Medium	dB(A)	34	34	35	38
			Low	dB(A)	28	28	29	33
			Silent operation	dB(A)	21	21	21	30
	Piping connections	Liquid	OD	mm	6.35	6.35	6.35	6.35
Gas		OD	mm	9.52	9.52	9.52	12.7	
Drain				18	18	18		
Control systems	Infrared remote control			ARC480A78	ARC480A78	ARC480A78	ARC480A78	
	Wired remote control			BRC073A1	BRC073A1	BRC073A1	BRC073A1	
Standard Accessories	Installation manual			1	1	1	1	
	AAA dry-cell batteries			2	2	2	2	
	General safety precautions			1	1	1	1	
	Operation manual			1	1	1	1	
	Titanium apatite deodorizing filter			1	1	1	1	
	Silver particle filter			1	1	1	1	
	Indoor unit fixing screws			2	2	2	2	
	Infrared remote control			1	1	1	1	
	Mounting plate			1	1	1	1	
	Remote control holder			1	1	1	1	
	Power supply	Phase			1~	1~	1~	1~
		Frequency		Hz	50	50	50	50
Voltage		V	220-240	220-240	220-240	220-240		
Notes				(1) - Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m	(1) - Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m	(1) - Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m	(1) - Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m	
				(2) - Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal)	(2) - Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal)	(2) - Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal)	(2) - Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal)	
				(3) - See separate drawing for electrical data	(3) - See separate drawing for electrical data	(3) - See separate drawing for electrical data	(3) - See separate drawing for electrical data	