

Specifications Table for RXA-A8

					RXA20A5V1B8	RXA25A5V1B8	RXA35A5V1B8
Dimensions	Unit		Height	mm	550	550	550
			Width	mm	840	840	840
			Depth	mm	350	350	350
Weight	Unit			kg	32	32	32
Compressor	Type				Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor
Operation range	Cooling	Ambient	Min.	°CDB	-10	-10	-10
			Max.	°CDB	46	46	46
	Heating	Ambient	Min.	°CWB	-15	-15	-15
			Max.	°CWB	18	18	18
Sound pressure level	Cooling		Nom.	dBA	46.0	46.0	49.0
	Heating		Nom.	dBA	47.0	47.0	49.0
Refrigerant	Type				R-32	R-32	R-32
	Charge			kg	0.76	0.76	0.76
	Charge			tCO2Eq	0.52	0.52	0.52
	GWP				675.0	675.0	675.0
Piping connections	Piping length	OU - IU	Max.	m	20	20	20
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)
	Level difference	IU - OU	Max.	m	15.0	15.0	15.0
Standard Accessories	Installation manual				1	1	1
	Refrigerant charge label				1	1	1
	Multilingual fluorinated greenhouse gases labels				1	1	1
	General safety precautions				1	1	1
	Drain plug				1	1	1
Power supply	Phase				1~	1~	1~
	Frequency			Hz	50	50	50
	Voltage			V	220-240	220-240	220-240