

Specifications Table for RXM-A

| | | | | RXM20A5V1B | RXM25A5V1B | RXM35A5V1B | RXM42A5V1B | RXM50A5V1B | RXM60A5V1B | RXM71A5V1B | |
|----------------------|--|-------------------------------|-----------|---------------------|--------------------------------------|--|--|--|--|--|--|
| Dimensions | Unit | Height | mm | 610 | 610 | 610 | 610 | 734 | 734 | 734 | |
| | | Width | mm | 923 | 923 | 923 | 923 | 954 | 954 | 954 | |
| | | Depth | mm | 367 | 367 | 367 | 367 | 401 | 401 | 401 | |
| Weight | Unit | | kg | 36 | 36 | 36 | 40 | 49 | 49 | 55 | |
| Fan motor | Speed | Cooling | Super low | rpm | 600 | 600 | 600 | 600 | 500 | | |
| Compressor | Type | | | | Hermetically sealed swing compressor | Hermetically sealed swing compressor | Hermetically sealed swing compressor | Hermetically sealed swing compressor | Hermetically sealed swing compressor | Hermetically sealed swing compressor | |
| Operation range | Cooling | Ambient | Min. | °CDB | -10 | -10 | -10 | -10 | -10 | -10 | -10 |
| | | | Max. | °CDB | 50 | 50 | 50 | 50 | 50 (1), 46 (1) | 50 | 46 |
| | Heating | Ambient | Min. | °CWB | -21 | -21 | -21 | -21 | -21 (1), -15 (1) | -21 | -15 |
| | | | Max. | °CWB | 18 | 18 | 18 | 18 | 18 | 18 | 18 |
| Sound pressure level | Cooling | | Nom. | dB(A) | 46 | 46 | 47 | 48 | 48 | 47 | |
| | Heating | | Nom. | dB(A) | 47 | 47 | 49 | 49 | 49 | 48 | |
| Refrigerant | Type | | | | R-32 | R-32 | R-32 | R-32 | R-32 | R-32 | |
| | Charge | | | kg | 0.95 | 0.95 | 0.95 | 0.95 | 1.1 | 1.15 | 1.15 |
| | Charge | | | tCO ₂ Eq | 0.65 | 0.65 | 0.65 | 0.65 | 0.75 | 0.78 | 0.78 |
| | GWP | | | | 675 | 675 | 675 | 675 | 675 | 675 | 675 |
| Piping connections | Piping length | OU - IU | Max. | m | 20 | 20 | 20 | 30 | 30 | 30 | |
| | | Additional refrigerant charge | | | kg/m | 0.02 (for piping length exceeding 10m) | 0.02 (for piping length exceeding 10m) | 0.02 (for piping length exceeding 10m) | 0.02 (for piping length exceeding 10m) | 0.02 (for piping length exceeding 10m) | 0.02 (for piping length exceeding 10m) |
| | Level difference | IU - OU | Max. | m | 15 | 15 | 15 | 20 | 20 | 20 | |
| Power supply | Phase | | | | 1~ | 1~ | 1~ | 1~ | 1~ | 1~ | |
| | Frequency | | | Hz | 50 | 50 | 50 | 50 | 50 | 50 | |
| | Voltage | | | V | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | |
| Standard Accessories | Installation manual | | | | 1 | 1 | 1 | 1 | 1 | 1 | |
| | Drain joint | | | | 1 | 1 | 1 | 1 | | | |
| | Refrigerant charge label | | | | 1 | 1 | 1 | 1 | 1 | 1 | |
| | Multilingual fluorinated greenhouse gases labels | | | | 1 | 1 | 1 | 1 | 1 | 1 | |
| | General safety precautions | | | | 1 | 1 | 1 | 1 | | | |
| | LOT10 Energy Label | | | | 1 | 1 | 1 | 1 | | | |
| | Drain cap | | | | 3 | 3 | 3 | 3 | 1 | 3 | 3 |
| | RXM50A5V1B | | | | | | | | 1 | | |
| Notes | | | | | | | | (1) - See separate drawing for operation range | (1) - See separate drawing for operation range | (1) - See separate drawing for operation range | |
| | | | | | | | | (2) - See separate drawing for electrical data | (2) - See separate drawing for electrical data | (2) - See separate drawing for electrical data | |
| | | | | | | | | (3) - Contains fluorinated greenhouse gases | (3) - Contains fluorinated greenhouse gases | (3) - Contains fluorinated greenhouse gases | |
| Standard Accessories | Drain plug | | | | | | | | 1 | 1 | |