

# Specifications Table for RXF-E

					RXF20E5V1B	RXF25E5V1B	RXF35E5V1B	RXF42E5V1B
Dimensions	Unit		Height	mm	556	556	556	556
			Width	mm	740	740	740	740
			Depth	mm	343	343	343	343
Weight	Unit			kg	24.0	24.0	24.0	28.0
Compressor	Type				Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor
Operation range	Cooling	Ambient	Min.	°CDB	-10	-10	-10	-10
			Max.	°CDB	48	48	48	48
	Heating	Ambient	Min.	°CWB	-15	-15	-15	-15
			Max.	°CWB	18	18	18	18
Sound pressure level	Cooling		High	dB(A)	46.0	46.0	48.0	48.0
	Heating		High	dB(A)	47.0	47.0	48.0	48.0
Refrigerant	Type				R-32	R-32	R-32	R-32
	Charge			kg	0.420	0.420	0.550	0.750
	Charge			tCO <sub>2</sub> Eq	0.280	0.280	0.370	0.510
	GWP				675.0	675.0	675.0	675.0
Piping connections	Piping length	OU - IU	Max.	m	20	20	20	20
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)
	Level difference	IU - OU	Max.	m	12.0	12.0	12.0	12.0
Standard Accessories	Installation manual				1	1	1	1
	Refrigerant charge label				1	1	1	1
	Multilingual fluorinated greenhouse gases labels				1	1	1	1
	General safety precautions				1	1	1	1
	Drain plug				1	1	1	1
Power supply	Phase				1~	1~	1~	1~
	Frequency			Hz	50	50	50	50
	Voltage			V	220-240	220-240	220-240	220-240