

The UK's leading supplier of air conditioning.
Trusted brands at wholesale prices direct to customer.

	iPAC Split Systems			
Indoor Model	iPAC-09WS-IN	iPAC-12WS-IN	iPAC-18WS-IN	iPAC-24WS-IN
Outdoor Model	iPAC-09WS-ODU	iPAC-12WS-ODU	iPAC-18WS-ODU	iPAC-24WS-ODU
Energy Efficiency Rating Cooling	A++	A++	A++	A++
Energy Efficiency Rating Heating	A+++	A+++	A+++	A+++
Power Rating (Ph-V-Hz)	1/220-240V/50Hz	1/220-240V/50Hz	1/220-240V/50Hz	1/220-240V/50Hz
Capacity BTU/h (Cooling) Kw	9000 / 2.8	12000 / 3.6	18000 / 5.2	24000 / 7.0
Capacity BTU/h (Heating) Kw	10000 / 2.6	13000 / 2.6	19000 / 4.1	25000 / 4.8
Power Input (W) (Capacity)	732(100~1240)	1213(130~1580)	1550(140~2300)	2600(420~3150)
Current Input (A) C/H	3.18 / 3.18	5.27 / 4.73	6.7 / 6.8	11.5 / 11
EER/SEER (BTU/hr.W)	SEER 6.3	SEER 6.1	SEER 7.4	SEER 6.1
COP/SCOP (W/W)	SCOP 4.0	SCOP 4.0	SCOP 4.0	SCOP 4.0
Indoor Noise Level SPL dB (A) (Max)	38.5	40.5	42.5	45
Outdoor Noise Level SPL dB (A) (Max)	55.5	56	56	59
Indoor Airflow (m3/h) (Hi/Mi/Lo)	466/360/325	540/430/314	840/680/540	980/817/662
Max. Current Rating C/H (A) Fuse Rating (Type D)	5.4 / 5.2	6.9 / 6.9	10 / 10.2	13.8 / 12.2
Net Dimension (mm) Indoor (WxDxH)	805x194x285	805x194x285	957x213x302	1040x220x327
Unit Dimension (mm) Outdoor (WxDxH)	720x270x495	720x270x495	805x330x554	890x342x673
Net Weight Indoor (Kg)	7.6	7.6	10	12.3
Net Weight Outdoor (Kg)	23.2	23.2	32.7	42.9
Max Room Size (m2)	12~18	16-23	24~35	32~47
Pipe Kit Included (Metre)	3M	3M	4M	5M
Copper Pipe Size (Inch)	1/4" & 3/8"	1/4" & 3/8"	1/4" & 1/2"	3/8" & 5/8"
Operating Temp Indoor (Cooling/Heating) °C	17~32 / 0~30	17~32 / 0~30	17~32 / 0~30	17~32 / 0~30
Indoor Packaging Size (mm) (WxDxH)	870x270x365	870x270x365	1035x295x385	1120x405x315
Indoor Gross Weight (kg)	9.7	9.8	13	15.8
Outdoor Gross Size (mm) (WxDxH)	835x300x540	835x300x540	915x370x615	995x398x740
Outdoor Gross Weight (kg)	25	25	35.4	45.9

